


Datasheet

Miniserver Gen. 1

Part No: 100001



About the product

The Loxone Miniserver serves as central control unit for all kinds of automation tasks. In addition to a LAN interface the device is equipped with the Loxone Link and other interfaces for expansion purposes.


Electrical Data

Power supply	18 ... 30VDC
Power consumption	typ. 2.1W, max. 4.32W (all Relays on)
Power loss at max. load	8.6W
Digital inputs	8 digital inputs logic 0: 0 ... 7.2VDC undefined: 7.2 ... 8.2VDC logic 1: 8.2 ... 24VDC (Ri=300kOhm)
Analogue inputs	4 analogue inputs 0 ... 10V, resolution 10 Bit when used as digital inputs: logic 0: 0 ... 0.9VDC undefined: 0.9 ... 1.5VDC logic 1: 1.5 ... 24VDC (Ri=10kOhm)
Outputs	8 digital outputs (relays), dry contact - 250VAC 5A at cosφ=1 - 30VDC 5A 4 analogue outputs: 0 ... 10V (max. 20mA peak, max. 10mA continuous), resolution 12 Bit
Interfaces	Loxone Link: connection with Extensions, up to 30 devices KNX: for integration of KNX devices LAN: 100Mbps, IPv4, HTTP only
Ambient temperature	0 ... 50°C / 32 ... 122°F
Humidity	max. 95% r.H. (non condensing)
Power reserve of internal clock in case of power failure	504 hours

Connections

	Power supply, Loxone Link, digital & analogue inputs, digital & analogue outputs	KNX interface
Wire cross-section	0.05 ... 2.5mm ² / AWG30 ... 12	0.25 ... 0.8mm ² / AWG23 ... 18
Stripping length	6 ... 7.5mm / 0.24 ... 0.30"	5mm / 0.2"
Torque of terminal blocks	0.5 ... 0.6Nm / 0.37 ... 0.44 lbf ft	-
Temperature resistance	min. 80°C / 176°F for IEC, min. 75°C / 167°F for UL	-40 ... 105°C / -40 ... 221°F

Connection Diagram




Product Characteristics

Mounting type	DIN rail according to EN50022, 35mm
Colours	Green: RAL6018
Finish	Matte

Weight & Dimensions

Net weight	327g
Total weight	372g
Product dimensions	157x88x57mm / 6.18x3.46x2.24" (LxWxH), 9 division units



Pack size	180x110x65mm / 7.08x4.33x2.56" (LxWxH)
-----------	--

Certifications & Standards

Safety rating	IP20
Operation	Type 1 (UL60730-1, CSA E60730-1)
Rated impulse voltage for digital output	2.5kV (UL60730-1, max. Altitude 2000m)
Degree of pollution	2
Software class	A

Certifications	UL60730-1 CSA E60730-1	RECOGNIZED COMPONENT ETL LISTED Intertek
	CE	

120 Ohm resistor

Please use the 120 Ohm resistor at the last Extension which is connected to the Loxone Link.

Installation must be carried out by a qualified electrician in accordance with the relevant regulations.


Published by
Loxone Electronics GmbH

Smart Home 1
4154 Kollerschlag
Austria
Tel: +43 7287 7070-0
loxone.com

Datenblatt

Miniserver Gen. 1

Art. Nr. 100001



Information zum Produkt

Der Loxone Miniserver dient als zentrale Steuereinheit für Automatisierungsaufgaben aller Art. Neben einer LAN Schnittstelle verfügt das Gerät u.a. über die Loxone Link Schnittstelle zur Erweiterung.


Elektrische Daten

Spannungsversorgung	18 ... 30VDC
Leistungsaufnahme	typ. 2.1W, max. 4.32W (alle Relais im Einsatz)
Verlustleistung bei max. Last	8,6W
Digitale Eingänge	8 digitale Eingänge logisch 0: 0 ... 7,2VDC undefiniert: 7,2 ... 8,2VDC logisch 1: 8,2 ... 24VDC (Ri=300kOhm)
Analoge Eingänge	4 analoge Eingänge 0 ... 10VDC, Auflösung 10 Bit bei Verwendung als digitale Eingänge: logisch 0: 0 ... 0,9VDC undefiniert: 0,9 ... 1,4VDC logisch 1: 1,4 ... 24VDC (Ri=10kOhm)
Ausgänge	8 digitale Ausgänge (Relais), potentialfrei - 250VAC 5A at cosφ=1 - 30VDC 5A 4 analoge Ausgänge: 0 ... 10V (max. 20mA kurzzeitig, max. 10mA Dauerstrom), Auflösung 12 Bit
Schnittstellen	Loxone Link: Verbindung mit Extensions, bis zu 30 Geräte KNX: zur Einbindung von KNX Geräten LAN: 100Mbps, IPv4, nur HTTP
Umgebungstemperatur	0 ... 50°C / 32 ... 122°F
Luftfeuchtigkeit	max. 95% r.H. (nicht kondensierend)
Gangreserve der internen Uhr bei Stromausfall	504 Stunden

Anschlüsse

	Spannungsversorgung, Loxone Link, digitale & analoge Eingänge, digitale & analoge Ausgänge	KNX Schnittstelle
Leiterquerschnitt	0,05 ... 2,5mm ² / AWG30 ... 12	0,25 ... 0,8mm ² / AWG23 ... 18
Abisolierlänge	6 ... 7,5mm / 0,24 ... 0,30"	5mm / 0,2"
Drehmoment der Klemmen	0,5 ... 0,6Nm / 0,37 ... 0,44 lbf ft	-
Temperaturbeständigkeit	min. 80°C / 176°F for IEC, min. 75°C / 167°F for UL	-40 ... 105°C / -40 ... 221°F

Anschlussplan




Produkteigenschaften

Montageart	Hutschiene nach EN50022, 35mm
Farbe	Grün: RAL6018
Glanzgrad	Matt

Gewicht & Abmessungen

Nettogewicht	327g
Bruttogewicht	372g
Produktmaße	157x88x57mm / 6,18x3,46x2,24" (LxBxH), 9 Teilungseinheiten



Packmaß	180x110x65mm / 7,08x4,33x2,56" (LxBxH)
---------	--

Zertifizierungen & Standards

Schutzart	IP20
Einsatzgebiet	Type 1 (UL60730-1, CSA E60730-1)
Bemessungsspannung der digitalen Ausgänge	2.5kV (UL60730-1, max. Höhe 2000m)
Verschmutzungsgrad	2
Software Klasse	A

Zertifizierungen	UL60730-1 CSA E60730-1   Intertek
------------------	--

120 Ohm Widerstand

Verwenden Sie bitte den 120 Ohm Widerstand an der letzten Extension, die am Loxone Link angeschlossen ist.

Die Installation muss nach den einschlägigen Vorschriften durch eine Elektrofachkraft erfolgen.

Veröffentlicht von
Loxone Electronics GmbH

Smart Home 1
 4154 Kollerschlag
 Austria
 Tel: +43 7287 7070-0
 loxone.com