Technical Specifications

| Power supply | via AC unit |
|----------------------|--|
| Power consumption | typ. 0.22W, max. 0.35W |
| Loxone Air interface | 868MHz (SRD Band Europe), 4 channels, max. 15.1mW e.r.p. 915MHz (ISM Band Region 2), 10 channels, max. 13.2mW internal antenna |
| Ambient Temperature | -20 65°C / -4 149°F |
| Humidity | max. 95% r.H. (non condensing) |
| Degree of protection | IP20 |
| | |

Connecting cable

| Wire cross-section | 0.34mm² / AWG22 |
|------------------------|-----------------|
| Temperature resistance | 80°C / 176°F |
| Length | 300mm / 11.81" |
| Part. No. | 000580 |



For more information about this product, visit loxone.com/help/AC-Control-Air-100558

An up-to-date List of compatible AC units is available online shop.loxone.com/ac-control/

Loxone Electronics GmbH Smart Home 1 4154 Kollerschlag Austria Loxone UK
The Forum
Station Road
Theale, RG7 4RA
United Kingdom



For additional information, declaration of conformity, visit www.loxone.com/datasheets

V0506

Need Help? loxone.com/support



LOXONE

AC Control Air for Mitsubishi Heavy Industries

Part No.: 100558

About the Product

With the AC Control Air for Mitsubishi Heavy Industries you can integrate Mitsubishi air conditioners easily, quickly and seamlessly into your Loxone installation. Intelligent control of the air conditioners can significantly increase comfort and reduce energy consumption by more than 30% at the same time. This saves costs and protects the planet.

No additional power supply necessary Simple commissioning via Plug & Play very compact design: 38.3x34.3x10,5mm incl. full user interface and control in the Loxone App



Installation may only be carried out with the power supply to the air conditioner switched off!

