

For more information about this product, visit

loxone.com/help/meter-reader-ir-air

Loxone Electronics GmbHSmart Home 1
4154 Kollerschlag
Austria

Loxone UK
The Forum
Station Road
Theale, RG7 4RA
United Kingdom



For additional information, declaration of conformity, visi loxone.com/datasheets

Need Help? loxone.com/support



LOXONE



Meter Reader IR Air

Part No: 100151

Technical Specifications

Power supply	14 24VDC or via Micro USB
Power consumption	Micro USB: typ. 0.1W external power supply: typ. 0.4V
Power loss at max. load	0.4W
Interfaces	Loxone Air: 868MHz (SRD Band Europe), 4 channels available 915MHz (ISM Band Region 2), 10 channels available max. Power 3.16mW
	supported protocols: AMIS IEC 62056-21 SML M-Bus
	supported meters: https://www.loxone.com/enen/ info/smart-energy-meter-list/
Ambient temperature	0 50°C / 32 122°F
Humidtiy	max. 95% r.H. (non condensing)
Safety rating	IP40


About the Product

The Loxone IR Meter Reader Air enables direct reading of compatible electric meters with infrared interface.

Information

Contains FCC ID: COR-ZWIR4512AC1
This device complies with part 15 of the FCC Rules.
Operation is subject to the following two conditions:

- 1. This device may not cause harmful interference
- This device must accept any interference received, including interference that may cause undesired operation



Be aware of the correct positioning of the connectors on the power meter.