Technical Specifications

4.4 5.25VDC via included micro USB power supply
typ. 1.3W, max. 1.3W
1.3W
Loxone Air: 868MHz (SRD Band Europe), 915MHz (ISM Band Region 2) max. Power 3.16mW internal antenna
Loxone Link: connection with up to 30 Extensions
LAN: 100Mbps, IPv4, HTTP only
0 50°C / 32 122°F
max. 95% r.H. (non condensing)
IP20
90x90x20mm / 3.54x3.54x0.79" (LxWxH)
The device is free of maintenance and may only be cleaned with a dry cloth.

LOXONE

Need Help?

loxone.com/support

Loxone Electronics GmbH Smart Home 1 4154 Kollerschlag Austria

loxone.com



X

Part No: 100139



Miniserver Go

LOXONE

About the product

The Miniserver Go is a device for the automatic control and management of home automation and similar non safety critical applications. The Loxone Miniserver Go has a fully integrated Air Base Extension and is perfect for retrofitting Loxone in existing homes.

Installation & electrical connection

If the unit is used in a non conform manner as specified by the manufacturer the product included safeguards will be impaired.

Information

Contains FCC ID: COR-ZWIR4512AC1 This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- 1. This device may not cause harmful interference
- 2. This device must accept any interference received, including interference that may cause undesired operation


Loxone Link Connection

Wire cross-section	0.2 1.5 mm² / AWG24 16
Striping length	8mm / 0.31″
Temperature resistance	-40 105°C / -40 221°F


Micro USB Connector



Specifications



Connect Extension



This folder is a part of the product!



For additional information, declaration of confirmity, visit www.loxone.com/help/miniserver-go